

# UltraGrip



## 2665

### PVC Cement

Medium Body • Fast Setting • Low VOC • Blue

#### DESCRIPTION

*UltraGrip* PVC Cement, 2665, is a Low-VOC solvent cement designed specifically for use in joining all types of PVC (PolyVinylChloride) pipe and fittings thru 6" diameter, Schedule 40 and Schedule 80, with interference fit. It is fast acting, high strength and has an excellent shelf life of three years from the date of manufacture.

Applications include potable drinking water, DWV (Drain/Waste/Vent), sewer and drain, irrigation, pool & spa, electrical conduit.

2665 is manufactured to the high standard of ASTM D 2564 to insure a quality product. A sample is kept from each batch to verify the quality of *UltraGrip* cements.

#### TECHNICAL DATA

<u>PRODUCT</u>	<u>BODY</u>	<u>COLOR</u>	<u>DENSITY</u>	Recommended Max. Pipe Diameter <u>All Schedules *</u>	<u>SET TIME</u>
2665	Medium	Blue	7.8 lb/gal	6"	Fast

Interference fit only

\*- Incl. Sch. 40 & 80

HYDROSTATIC BURST STRENGTH: 400 psi minimum (73° F, 2 hr. cure)

LAP SHEAR STRENGTH: 900 psi minimum (73° F, 72 hr. cure)

SPECIFICATIONS: ASTM D 2564

FLASH POINT: 6° F (closed cup)

SHELF LIFE: 3 year minimum

LISTINGS: NSF (National Sanitation Foundation) 

U.P. Code (Uniform Plumbing Code)

VOC INFORMATION: Max VOC per SCAQMD 1168/316 : 510 g/l